

PEWOFLEX ø 172-1370 mm / PN16 (EPDM)

Order number: 138-F10A4E172-185



Diameter range: > 172 mm

Pipe materials: Metal pipes - Metal pipes, Plastic pipes - Plastic pipes, Metal pipes - Plastic pipes, All pipe materials

Flowing medium: Drinking water / wastewater / air / compressed air (oil-free) / solids -30 °C up to 125 °C EPDM HT (peroxyd)

Pressure levels: PN 16

High tension-proof / Not tension-proof: Not tension-proof

Application temperature: -30°C bis +80°C

Maximum diameter difference: bis 3 mm

Tender text:

PEWOFLEX PN 16 NOT TENSION-PROOF with EPDM Sealing
-30°C up to +80°C in A4 (316/1.4571) Quality Ø min./max.

172-185 mm Width 138 mm 1 Closure Country of origin: NL

TARIC: 73072980 weight: 4 kg

OD Ø min. / max. 172 / 185 mm

≈ B 138 mm

Cmax 40 mm


≈ d 230 mm

≈ H 258 mm

M M12

Gewicht 4 kg

≈ Volumen 13 dm³



Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).

PEWOBAR GmbH | Barloer Straße 34 | D-46414 Rhede | Fon: +49 (0) 2872 3075930 | www.pewobar.de

Geschäftsführer: Dipl.-Ing. Wolfgang Barbett | Amtsgericht Coesfeld HRB 9285 | Ust.ID Nr.: De 237757754 | eMail: wb@pewobar.de
Bankverbindung: Volksbank Rhede | Konto: 53063400 | BLZ 428 618 14 | IBAN: DE 60 428 618 140 053 063 400 | BIC: GENODEM1RHD