

PEWOFLEX ø 277-1471 mm / PN10 (NBR)

Order number: 138-F6A4N277-290



Diameter range: > 172 mm

Pipe materials: Metal pipes - Metal pipes, Plastic pipes - Plastic pipes, Metal pipes - Plastic pipes, All pipe materials

Flowing medium: Water / flammable gases / compressed air / oil / fuel and other hydrocarbons -20 °C bis +80 °C NBR

Pressure levels: PN 10

High tension-proof / Not tension-proof: Not tension-proof

Application temperature: -20°C bis +80°C
Maximum diameter difference: bis 3 mm

Tender text:
 PEWOFLEX PN 10 NOT TENSION-PROOF with NBR Sealing
 -20°C up to +80°C in A4 (316/1.4571) Quality Ø min./max.
 277-290 mm Width 138 mm 1 Closure Country of origin: NL
 TARIC: 73072980 weight: 5 kg

OD Ø min. / max. 277 / 290 mm

≈ B 138 mm

Cmax 40 mm


≈ d 332 mm

≈ H 360 mm

M M12

Gewicht 5 kg

≈ Volumen 24 dm³



Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).