PEWOCLAMP ø 19-843 mm / PN16 (VITON) A2

Order number: 75HQS-16A2V19-23

Damage length:	Damage length up to max. 400 mm all damages
Flowing medium:	Mineral oils / aliphatic / aromatic hydrocarbons / chlorinated hydrocarbons / concentrated and diluted acids, weak alkalis -20 °C bis 200 °C FKM / VITON®
Housing material:	Closure, Housing Material A2 (1.4301)

Application temperature: -10°C bis +200°C

Tender text:
PEWOCLAMP one-piece Repair clamp with one screw plug per closure, pressure range: PN 16 width: 75 mm Ø min./max.: 19-23 Stainless Steel Quality: Closure, Housing Material A2 (1.4301) max. 10 mm damage length Waffle structure seal Viton temperature range: -10°C up to +200°C / Country of origin: NL TARIC: 73072980

OD Ø min. / max.	19-23 mm
≈ B	75 mm
Cmax	10 mm
M	M12

PEWOBAR GmbH | Barloer Straße 34 | D-46414 Rhede | Fon: +49 (0) 2872 3075930 | www.pewobar.de
Geschäftsführer: Dipl.-Ing. Wolfgang Barbett | Amtsgericht Coesfeld HRB 9285 | Ust.ID Nr.: De 237757754 | eMail: wb@pewobar.de
Bankverbindung: Volksbank Rhede | Konto: 53063400 | BLZ 428 618 14 | IBAN: DE 60 428 618 140 053 063 400 | BIC: GENODEM1RHD