

PEWOREPGRIP Ø 36-745 mm / PN25 (EPDM) A4

Order number: RG16A4E36-39



Diameter range:	<= 172 mm, > 172 mm
Housing material:	Closure, Housing Material A4 (1.4571 / 1.4404)
Pipe materials:	Metal pipes - Metal pipes
Flowing medium:	Drinking water / wastewater / air / compressed air (oil-free) / solids -30 °C up to 125 °C EPDM HT (peroxyd)
Pressure levels:	PN 50
High tension-proof / Not tension-proof:	High tension-proof

Application temperature: -30°C bis +125°C

Maximum diameter difference: bis 1 mm

Tender text:

PEWOREPGRIP PN 50 TENSION-PROOF with EPDM Sealing
-30°C up to +125°C in A4 (316/1.4571) Quality Ø min./max. 36-39 mm Width 60 mm 1 Closure / Country of origin: NL TARIC: 73072980 weigth: 0,4 kg

OD Ø min. / max.	36 / 39 mm
≈ B	60 mm
Cmax	15 mm
≈ d	66 mm
≈ H	104 mm
M	M8
Gewicht	0.4 kg
≈ Volumen	1 dm³

Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).