

## PEWOREPGRIP ø 36-745 mm / PN25 (NBR) A4

Order number: RG16A4N36-39



<b>Diameter range:</b>	<= 172 mm
<b>Housing material:</b>	Closure, Housing Material A4 (1.4571 / 1.4404)
<b>Pipe materials:</b>	Metal pipes - Metal pipes Water / flammable gases / compressed air / oil / fuel and other hydrocarbons -20 °C bis +80 °C
<b>Flowing medium:</b>	NBR
<b>Pressure levels:</b>	PN 50
<b>High tension-proof / Not tension-proof:</b>	High tension-proof

**Application temperature:** -20°C bis +80°C

**Maximum diameter difference:** bis 1 mm

**Tender text:**

PEWOREPGRIP PN 50 TENSION-PROOF with NBR Sealing  
-20°C up to +80°C in A4 (316/1.4571) Quality Ø min./max. 36-39 mm Width 60 mm 1 Closure / Country of origin: NL TARIC: 73072980 weigth: 0,4 kg

<b>OD Ø min. / max.</b>	36 / 39 mm
<b>≈ B</b>	60 mm
<b>Cmax</b>	15 mm
<b>≈ d</b>	66 mm
<b>≈ H</b>	104 mm
<b>M</b>	M8
<b>Gewicht</b>	0.4 kg
<b>≈ Volumen</b>	1 dm <sup>3</sup>

**Important information:**

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).