

PEWOUNIGRIP Ø 39-430 mm / PN16 (NBR)

Order number: 250-UG16GGG50N39-52



Diameter range:	39 bis 430 mm
Pipe materials:	Stahl / Duktiler Guß / PE / PB / PP / PVC / ABS / Asbestzement
Flowing medium:	Trinkwasser / Abwasser / Luft / Druckluft (ölfrei) / Feststoffe -30 °C bis +60 °C NBR
Pressure levels:	PN 16
High tension-proof / Not tension-proof:	High tension-proof

Application temperature: -20°C bis +60°C

Maximum diameter difference: 13

Tender text:

PEWOUNIGRIP PN 16 Axial Restrained Coupling with NBR
Sealing -20°C up to +60°C in GGG 50 Quality acc. to EN-GJS-500-7 Resicoat epoxy coating (200 my) blue colour to DIN 30677 Ø min./max. 39-52 mm width 250 mm 2 flanges Country of Origin: EU TARIC Code: 73071990 weight: 5,1 kg

OD Ø min. / max.	39 / 52 mm
≈ B	250 mm
M	M12
Gewicht	5.1 kg

Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid pipes with a minimum wall thickness are used under static load.
- !!!Install with a minimum pipe distance of 20 mm!!
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).