

## PEWOUNIGRIP-Ø 39-430 mm / PN16 (NBR) FA DN 50-400

Order number: 135-FA50UG16GGG50N39-52



|                                                |                                                                                       |
|------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Diameter range:</b>                         | 39 bis 430 mm                                                                         |
| <b>Pipe materials:</b>                         | Stahl / Duktiler Guß / PE / PB / PP / PVC / ABS / Asbestzement                        |
| <b>Flowing medium:</b>                         | Trinkwasser / Abwasser / Luft / Druckluft (ölfrei) / Feststoffe -30 °C bis +60 °C NBR |
| <b>Pressure levels:</b>                        | PN 16                                                                                 |
| <b>High tension-proof / Not tension-proof:</b> | High tension-proof                                                                    |

**Application temperature:** -20°C bis +60°C  
**Maximum diameter difference:** 13

**Tender text:**  
 PEWOUNIGRIP PN 10/16 Axial Restrained flange adaptor DN 50 with NBR Sealing -20°C up to +60°C in GGG 50 Quality acc. to EN-GJS-500-7 Resicoat epoxy coating (200 my) blue colour to DIN 30677 Ø min./max. 39-52 mm width 135 mm 1 flange Country of Origin: EU TARIC Code: 73071990 weight: 4,1 kg

|                         |            |
|-------------------------|------------|
| <b>OD Ø min. / max.</b> | 39 / 52 mm |
| <b>≈ B</b>              | 135 mm     |
| <b>M</b>                | M12        |
| <b>Gewicht</b>          | 4.1 kg     |

### Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid pipes with a minimum wall thickness are used under static load.
- !!!Install with a minimum pipe distance of 20 mm!!
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).