

PEWOCOMBIGRIP Ø 39-363 mm / PN16 (NBR) | 0039 / 43 mm | 060mm

Product number CGS16A4N39-43




Pressure levels	PN 16
Pipe materials	Metal pipes - Plastic pipes
Diameter range	> 172 mm
Flowing medium	Water / flammable gases / compressed air / oil / fuel and other hydrocarbons -30 °C bis +80 °C NBR
High tension-proof / Not tension-proof	High tension-proof

Application temperature: -20°C up to +80°C

Maximum diameter difference: up to 1 mm

PEWOCOMBIGRIP PN 16 TENSION-PROOF with NBR Sealing -20°C up to +80°C
in A4 (316/1.4571) Quality Ø min./max. 39-43 mm Width 60 mm 1 Closure
Country of origin: NL TARIC: 73072980 weighth: 0,6 kg

OD Ø min. / max.	39 / 43 mm
B	60 mm
Cmax	15 mm
d	66 mm
H	104 mm
M	M8
Weight	0.6 kg



Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).