

## PEWOREP ø 36-172 mm / PN25 (NBR) 2 teilig

**Product number** 2RS16A4N156-172



|                         |                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------|
| <b>Flowing medium</b>   | Water / flammable gases / compressed air / oil / fuel and other hydrocarbons -30 °C bis +80 °C NBR |
| <b>Housing material</b> | Closure, Housing Material A4 (1.4571 / 1.4404)                                                     |
| <b>Damage length</b>    | Damage length up to max. 400 mm all damages                                                        |

PEWOREP PN 25 NOT TENSION-PROOF with NBR Sealing -20°C up to +80°C in A4 (316/1.4571) Quality Ø min./max. 156-172 mm Width 110 mm 2 Closure / Country of origin: NL TARIC: 73072980 weigh: 2,5 kg

**Weight** 2.5 kg

### Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).