

## PEWOX ø 43-770 mm / PN 24 / 16 (EPDM) A2 | max. 100 mm | 43 / 60

**Product number** 140-2POX24A2E43-60



<b>High tension-proof / Not tension-proof</b>	Not tension-proof
<b>Diameter range</b>	> 172 mm
<b>Pipe materials</b>	All pipe materials
<b>Housing material</b>	Closure, Housing Material A2 (1.4301)
<b>Pressure levels</b>	PN 24 / 16 / 12
<b>Flowing medium</b>	Drinking water / wastewater / air / compressed air (oil-free) / solids -30 °C bis +60 °C EPDM

**Application temperature:** -30°C bis +60°C

**Maximum diameter difference:** bis 8 mm

PEWOX two-piece Repair clamp with 4 screw plug, pressure range: PN 24width: 140 mm damage length: max. 100 mm Ø min./max.: 43-60 mm Ø difference max: 8 mm Steel Quality: Closure, Housing Material A2 (1.4301 / 304) dynamic seal EPDM sulfur cured temperature range: -30°C bis +60°C Country of Origin: EU / TARIC: 73072980 weight:

<b>OD Ø min. / max.</b>	43 / 60 mm
<b>B</b>	140 mm
<b>Cmax</b>	100 mm
<b>M</b>	M12

### Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).