

PEWOX ø 43-770 mm / PN 24 / 16 (EPDM) A4 | max. 100 mm | 43 / 60

Product number 140-2POX24A4E43-60



High tension-proof / Not tension-proof	Not tension-proof
Diameter range	> 172 mm
Pipe materials	All pipe materials
Pressure levels	PN 24 / 16 / 12
Flowing medium	Drinking water / wastewater / air / compressed air (oil-free) / solids -30 °C bis +60 °C EPDM
Housing material	Closure, Housing Material A4 (1.4571 / 1.4404)

Application temperature: -30°C bis +60°C

Maximum diameter difference: bis 8 mm

PEWOX two-piece Repair clamp with 4 screw plug, pressure range: PN 24width: 140 mm damage length: max. 100 mm Ø min./max.: 43-60 mm Ø difference max: 8 mm Steel Quality: Closure, Housing Material A4 (1.4571 / 1.4404 / 316Ti / 316 L) dynamic seal EPDM sulfur cured temperature range: -30°C bis +60°C Country of Origin: EU / TARIC: 73072980 weight:

OD Ø min. / max.	43 / 60 mm
B	140 mm
Cmax	100 mm
M	M12

Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).