

PEWOUNIGRIP-Ø 39-430 mm / PN16 (NBR) FA DN 50-400 | 039 / 052 mm | 50

Product number 135-FA50UG16GGG50N39-52



Pressure levels	PN 16
High tension-proof / Not tension-proof	High tension-proof
Pipe materials	Steel / Ductile iron / PE / PB / PP / PVC / ABS / Asbestos cement
Diameter range	39 bis 430 mm
Flowing medium	oil and other Hydrocarbons / wastewater / air / compressed air / solids -20 °C up to +60 °C NBR

Application temperature: -20°C up to +60°C

Maximum diameter difference: 13 mm

PEWOUNIGRIP PN 10/16 Axial Restrained flange adaptor DN 50 with NBR Sealing -20°C up to +60°C in GGG 50 Quality acc. to EN-GJS-500-7 Resicoat epoxy coating (200 my) blue colour to DIN 30677 Ø min./max. 39-52 mm width 135 mm 1 flange Country of Origin: EU TARIC Code: 73071990 weigth: 4,1 kg

OD Ø min. / max.	39 / 52 mm
B	135 mm
M	M12
Weight	4.1 kg

Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications.
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid pipes with a minimum wall thickness are used under static load.
- !! Install with a minimum pipe distance of 20 mm !!
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).