

PEWOREP Ø 172-1370 mm / PN16 (NBR) | 290mm | 0719 / 745 mm

Product number 287-2R10A4N719-745




Pressure levels	PN 16
High tension-proof / Not tension-proof	Not tension-proof
Diameter range	> 172 mm
Pipe materials	All pipe materials
Flowing medium	Water / flammable gases / compressed air / oil / fuel and other hydrocarbons -30 °C bis +80 °C NBR
Housing material	Closure, Housing Material A4 (1.4571 / 1.4404)

Application temperature: -20°C bis +80°C

Maximum diameter difference: bis 3 mm

PEWOREP PN 16 NOT TENSION-PROOF with NBR Sealing -20°C up to +80°C in A4 (316/1.4571) Quality Ø min./max. 719-745 mm Width 287 mm 2 Closure / Country of origin: NL TARIC: 73072980 weigh: 36 kg

OD Ø min. / max.	719 / 745 mm
B	287 mm
Cmax	100 mm
d	802 mm
H	835 mm
M	M16
Weight	36 kg



Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).