

PEWOPLASTGRIP Ø 72-515 mm / PN10 (EPDM) | 095mm | 0088 / 96 mm

Product number PGS10A4E88-96




Pipe materials	Plastic pipes - Plastic pipes
Diameter range	> 172 mm
Pressure levels	PN 10
High tension-proof / Not tension-proof	High tension-proof
Flowing medium	Drinking water / wastewater / air / compressed air (oil-free) / solids -30 °C up to 125 °C EPDM HT (peroxyd)

Application temperature: -30°C up to +125°C

Maximum diameter difference: up to 1 mm

PEWOPLASTGRIP PN 10 TENSION-PROOF with EPDM Sealing -30°C up to +125°C in A4 (316/1.4571) Quality Ø min./max. 88-96 mm Width 95 mm 1 Closure Country of origin: NL TARIC: 73072980 weight: 1,1 kg

OD Ø min. / max.	88 / 96 mm
B	95 mm
Cmax	30 mm
d	124 mm
H	170 mm
M	M10
Weight	1.1 kg



Important information:

- Follow the installation and disassembly instructions.
- PN = Working pressure with consideration of the application loads for industrial applications. In case of shipbuilding applications, PN is one PN class below, e.g. PN 25 Industry = PN 16 Shipbuilding.
- PN classes = PN 2.5; PN 6; PN 10; PN 16; PN 25
- Test pressure = PN x 1.5
- The pressure data is given under the precondition that radially rigid steel pipes with a minimum wall thickness are used under static load.
- Use the Technical Manual for other pipe materials.
- Band inserts are necessary for special applications.
- Support sleeves must be used for thermoplastic plastic pipes (PE/PP/PB/PVC/ABS...).